



COD	G-AHRV-200/4	G-AHRV-500/4	G-AHRV-1000/4	G-AHRV-2000/4	G-AHRV-4000/4	G-AHRV-5000/4
Volum (m3/h)	200 m3/h	500 m3/h	1000 m3/h	2000 m3/h	4000 m3/h	5000 m3/h
Volum (CFM)	118	294	588	1176	2353	2941
Presiune statică externă (Pa)	75	80	130	170	220	240
Sursa de alimentare (V~,Hz,Ph)	220~240,50,1	220~240,50,1	220~240,50,1	380~415,50,3	380~415,50,3	380~415,50,3
Putere de intrare W	65	220	510	1215	2415	3122
Temp. Eficiență %	77-78	79	78	79	78-79	66-69
Transfer termic %	64-69	66-71	67-71	68-70	67-71	79-80
Nivel de zgomot (dB)	37	41	45	60	66	68
Flanșă (mm)	Φ 144	Φ 194	Φ 242	320x300	500x690	500x690
Greutate netă (kg)	25	41	82	200	270	265
Greutate bruta (kg)	48	72	125	260	335	330
Dimensiune netă (LxPxH) (mm)	848x654x262	1018x1027x270	1274x1007x388	1600x1265x540	1725x1450x1050	1725x1450x1050
Dimensiune bruta (LxPxH) (mm)	896x702x312	1062x1060x318	1345x1065x558	1668x1331x720	1825x1550x1255	1825x1550x1255