



**Indoor Unit**

Model			<b>G-AMWM-H09</b>	<b>G-AMWM-H12</b>	<b>G-AMWM-H18</b>
Capacity	Cooling	BTU/h	9000 (4780-11 260)	12 000 (5800-12625)	17 980 (8530-19 790)
		kW	2.64 (1.40-3.30)	3.52( 1.70-3.70)	5.27 (2.50-5.80)
	Heating	BTU/h	10 000 (4095-10 240)	13 000 (6930-15 080)	18 350(7680-19 790)
		kW	2.93 (1.20-3.00)	3.81 (2.03-4.42)	5.27 (2.50-5.80)
Electric Data	Power Supply	V~,Hz,Ph	220~240,50,1	220~240,50,1	220~240,50,1
	Cooling Power Input	W	40	40	63
	Heating Power Input	W	40	40	63
Performance	Air Flow Volume	CFM	353	353	530
		m3/h	600	600	900
	Sound Pressure Noise Level	dB(A)	40/38/34	41/39/35	46/42/36
	Sound Power Noise Level	dB(A)	55	55	58
Dimension	Net Dimension (W*D*H)	mm	788*292*198	788*292*198	936*316*221
	Packing Dimension (W*D*H)	mm	880*370*290	880*370*290	1010*385*307
Weight	Net	kg	8	8	10
	Gross	kg	10	10	13
Pipe Diameter	Liquid Side	mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)
	Gas Side	mm(inch)	9.52(3/8)	9.52(3/8)	12.7(1/2)
	Drainage	mm	16.9	16.9	45551
Stuffing Quantity	20/40/40H	Unit	330/689/778	330/689/778	262/532/602